

Vaisala Surface Patrol Pavement Temperature Sensor with Display DSP100 Series



Benefits

- Mobile sensor provides pavement data for your entire route
- Real-time pavement and air temperature readings
- Inexpensive compared to other pavement monitoring methods

Features

- Measures both air and pavement temperatures
- Easy-to-read, dash-mounted digital display
- Patented cone design to protect sensor lens
- Separate air sensor for improved accuracy
- Quick and easy to install
- Unit can be calibrated in the field as opposed to returning it to the manufacturer
- Integrates with other vehicle equipment such as spreaders or distance measuring instruments
- Optional RS-232 output to connect to a computer or analog output for other applications

The Vaisala Surface Patrol Pavement Temperature Sensor with Display DSP100 Series is a mobile temperature sensor used to detect possible freezing temperatures on the pavement. It features a non-contact infrared sensor for measuring pavement temperature, and also measures air temperature. The easy-to-use DSP100 is valuable for large agencies, such as Departments of Transportation, all the way down to smaller companies with only a few trucks.

The DSP100 is mounted outside your vehicle and continuously monitors road surface temperatures, providing instant feedback on road

surface conditions. The DSP100 has a separate air temperature sensor and cabling so that it can be placed away from direct sunlight for accurate readings. The data retrieved from the DSP100 is accurate and real-time, making it a reliable method for collecting pavement information. The DSP100 can be calibrated in the field, ensuring you are always getting the most accurate readings. In addition, the pavement probe features a cone design to protect the sensor from spray and winter elements that can decrease the accuracy of the readings.

Technical data

General

Accuracy	±0.28 °C (0.5 °F) at 0 °C (32 °F)
Shock	50 Gs
Vibration	10 Gs in any axis
Input Voltage	12 or 24 VDC unregulated
Field Calibration	Adjustable ±17.5 °C (5.0 °F) at 0 °C (32 °F)
Optics	Precision crystal (germanium lens)
Air Temperature Cable Length	5.5 meters (18 feet) standard
Operating Air Temperature	-40 °C to +71.1 °C (-40 °F to +160 °F)
Dual Digital Meter	High brightness red LED, showing both air and pavement temperature
RF Hardened	Withstands external radio frequency effects caused by mobile radios
Digital Output*	RS-232; ASCII output
Analog Output*	4 to 20 mA; 1 to 5 V

CE COMPLIANCE
Directive 2004/104/EC

*Optional

Applications

- Winter maintenance operations (snow plows, supervisor vehicles, etc.)
- Other fleet vehicles to increase your AVL network

DSP100 Series

PRODUCT

DSP110
DSP111
DSP112
DSP113
DSP114



VAISALA

For more information, visit
www.vaisala.com or contact
us at sales@vaisala.com

Ref. B210979EN-A ©Vaisala 2010
This material is subject to copyright protection, with all
copyrights retained by Vaisala and its individual partners. All
rights reserved. Any logos and/or product names are trademarks
of Vaisala or its individual partners. The reproduction, transfer,
distribution or storage of information contained in this brochure
in any form without the prior written consent of Vaisala is strictly
prohibited. All specifications — technical included — are subject
to change without notice.

